

MODEL	HP	RPM	MAX BHP	MAX SONES	STATIC PRESSURE (in. wg) / Airflow (CFM)						
					0.000	0.100	0.125	0.250	0.375	0.500	0.625
H-245E-11	1	1160	1.12	21.1	5619	5549	5481	5129	4928	4512	4263
H-245E-17	1	1750	1.09	26.0	6050	5686	5598	5394	5185	4644	4593
H-246E-17	1.5	1750	1.6	22.7	6636	6589	6519	6169	5818	5652	5493
H-247E-17	2	1750	2.06	24.3	5728	5539	5485	5150	4962	4616	4412
H-305E-8	1	860	1.07	19.7	7493	7336	7183	6720	5730	5056	
H-305E-11	1	1160	1.11	34.4	7896	7740	7578	6798	6376	5920	5375
H-306E-11	1.5	1160	1.68	24.3	8995	8394	8232	7959	7587	7207	
H-307E-11	2	1160	1.89	26.0	9118	9049	8885	8004	7693	7256	6814
H-365E-8	1	860	1.12	24.3	11123	10570	10311	9314	8123		
H-366E-8	1.5	860	1.47	24.3	12006	11464	11163	10184	8954		
H-367E-8	2	860	1.87	24.3	13236	11921	11541	10529	10092		
H-365E-11	1	1160	0.98	34.4	9308	8850	8671	7957	6868	5845	4756
H-366E-11	1.5	1160	1.61	42.3	11899	11506	11299	10600	9343	8310	7077
H-367E-11	2	1160	1.99	45.4	12905	12602	12303	11050	10208	9170	7961
H-368E-11	3	1160	2.98	39.5	14419	13828	13464	12444	11777	10610	
H-425E-8	1	860	0.95	34.4	10948	10307	10069	9059	7487	6072	
H-426E-8	1.5	860	1.46	34.4	13371	12795	12567	11758	10452	9340	8026
H-427E-8	2	860	2.01	45.4	16279	15166	14838	13849	12659	11145	9374
H-428E-8	3	860	3.18	34.4	18559	18019	17448	14950	13947	13661	
H-486E-8	1.5	860	1.7	52.1	18385	17195	16529	14136	12429		
H-487E-8	2	860	2.15	48.6	19405	18515	18021	16399	14362	12953	
H-488E-8	3	860	2.98	48.6	20969	20618	20012	18249	15965	13384	
H-489E-8	5	860	5.02	73.7	23675	23640	23166	21913	20612	19728	18102