

MODEL	HP	RPM	MAX BHP	MAX SONES	STATIC PRESSURE (in. wg) / Airflow (CFM)						
					0.000	0.100	0.125	0.250	0.375	0.500	0.625
H-245S-11	1	1160	1.14	21.1	5063	5037	5014	4609	4545	4059	3844
H-245S-17	1	1750	1.09	27.9	5394	5109	5042	4698	4642	4258	4103
H-246S-17	1.5	1750	1.6	27.9	6003	5939	5867	5480	5051	4972	4924
H-305S-8	1	860	1.07	18.4	6099	6029	5961	5803			
H-305S-11	1	1160	1.12	34.4	6667	6614	6566	5724	5591	5261	4809
H-306S-11	1.5	1160	1.68	26.0	7521	6745	6536	6120	5958	5806	
H-307S-11	2	1160	1.89	27.9	8170	7396	7182	5954			
H-365S-8	1	860	1.12	26.0	10564	10058	9783	8994	7759		
H-366S-8	1.5	860	1.47	26.0	10914	10613	10262	9342	8027		
H-367S-8	2	860	1.87	24.3	12165	10607	10129				
H-365S-11	1	1160	0.98	34.4	9123	8671	8481	7797	6673	5732	4696
H-366S-11	1.5	1160	1.61	42.3	11347	11032	10817	10127	8790	7967	6722
H-367S-11	2	1160	1.99	45.4	12124	11893	11644	10279	9488	8565	7599
H-368S-11	3	1160	2.98	39.5	12160	11991	11518	11203	10191		
H-425S-8	1	860	0.95	34.4	10727	10116	9861	8934	7335	5968	
H-426S-8	1.5	860	1.47	34.4	12930	12567	12345	11520	10164	9077	7855
H-427S-8	2	860	2.01	45.4	15536	14263	13933	13032	11878	10644	
H-428S-8	3	860	3.18	36.8	16489	16303	16130	13089			
H-486S-8	1.5	860	1.7	52.1	16706	15644	14886	12541	11541		
H-487S-8	2	860	2.15	48.6	17625	17104	16539	14970	13039	12263	
H-488S-8	3	860	2.98	48.6	19174	18399	17662	15233	13570		
H-489S-8	5	860	5.02	73.7	20990	20785	20217	19427	19002	17534	