



Project Number:
Project Name:
Customer:
Date:

MODEL	DIMENSIONS (in.)					WEIGHT (lbs.)
	A	B	C	D	DIAMETER	
RSV-8	18.5	19.25	8	3	8.5	14
RSV-10	18.5	21.50	8.75	3.5	10.5	15
RSV-12	20.5	26	10.375	3.75	12.5	19
RSV-14	24.75	27.5	11.25	4.25	14.5	21
RSV-16	24.75	29.5	11.25	4.25	16.5	23
RSV-18	28.375	33.5	11.50	4.50	18.5	26
RSV-20	28.375	36.5	11.75	4.75	20.5	27
RSV-24	33.50	39.5	12.50	5.50	24.5	30
RSV-30	36.50	48	15.25	6.25	30.5	44
RSV-36	44.50	56	15.25	6.25	36.5	48

STANDARD FEATURES

- Compatible with spun dome power roof ventilators.
- Ideal for gravity relief or intake applications.
- Designed for minimum resistance to airflow.
- Heavy gauge aluminum shroud with a beaded edge.
- Aluminum housing with stainless steel fasteners to ensure superior corrosion resistance and long life.
- Aluminum bird screens.
- Detachable covers to easily access unit interior.

OPTIONAL FEATURES

Relief backdraft damper:

Upflow.

Downflow.

Motorized damper 115v.

Epoxy coating.

QTY	MODEL	AIR FLOW	WIND SPEED	STACK HEIGHT	TEMPERATURE DIFFERENCE