S445-JE Wall Louver
SUBMITTAL

Moffitt Ventilation Solutions



Project Number: _____

Project Name: _____

Customer: _____

Date: _____

Standard Features

- Frame depth: 4-in.
- Blade angle: 45°, Stationary
- Blade profile: Non-drainable ("J" style)
- Material: Extruded aluminum: 0.081-in., mill finish, 6063-T5
- Mounting clips and fasteners to attach clip to louver are included, shipped loose
- Mullion covers

Optional Features

Construction
- ☐ Welded 6063-T5 extruded aluminum

Frame Options
- ☐ 1.5-in. flanged frame
- ☐ Stucco flange
- ☐ Glazing frame
- ☐ Frame closure.
- ☐ Hinged frame
- ☐ Subframe

Finish options
- ☐ Polyester powder
- ☐ Baked enamel

Screen Options
- ☐ Bird screens
- ☐ Insect screens

Additional Options
- ☐ Blank-off panels: insulated or uninsulated
- ☐ Filter racks
- ☐ Burglar bars
- ☐ Factory-mounted electric or pneumatic actuator
- ☐ Low-leakage seals

Installation hardware and materials
- ☐ Clip angles
- ☐ Continuous angles
- ☐ Head/jamb/sill flashing

TAG	QTY	WIDTH	DEPTH	HEIGHT

(904) 241-9944 | MoffittCorp.com

Moffitt continuously improves our products. Specifications and dimensions are subject to change.
®The Moffitt logo is a registered trademark of Moffitt in the U.S., Mexico, and Canada. | ©2026 Moffitt. All rights reserved. Version 1 | October 2026

S445-JE Wall Louver
PERFORMANCE

Moffitt Ventilation Solutions

Free Area Chart (ft^2)

Height (in.) \ Width (in.)	12	18	24	30	36	42	48	54	60	66	72	78	84	90	96	102	108	114	120
12	0.3	0.5	0.6	0.8	1	1.2	1.3	1.5	1.7	1.9	2	2.2	2.4	2.6	2.7	2.9	3.1	3.3	3.4
18	0.5	0.8	1.1	1.4	1.7	2	2.3	2.6	2.9	3.2	3.5	3.8	4.2	4.5	4.8	5.1	5.4	5.7	6.0
24	0.7	1.2	1.6	2	2.5	2.9	3.3	3.7	4.2	4.6	5	5.5	5.9	6.3	6.8	7.2	7.6	8.1	8.5
30	1	1.7	2.3	2.9	3.6	4.2	4.8	5.4	6.1	6.7	7.3	7.9	8.6	9.2	9.8	10.4	11.1	11.7	12.3
36	1.3	2.1	2.9	3.7	4.5	5.3	6.1	6.9	7.7	8.5	9.2	10	10.8	11.6	12.4	13.2	14.0	14.8	15.6
42	1.6	2.5	3.5	4.4	5.4	6.3	7.3	8.2	9.2	10.1	11	12	12.9	13.9	14.8	15.8	16.7	17.7	18.6
48	1.8	2.9	3.9	5	6.1	7.2	8.1	9.3	10.4	11.5	12.5	13.6	14.7	15.8	16.8	17.9	19.0	20.1	21.1
54	2	3.2	4.4	5.6	6.8	8	9.2	10.4	11.6	12.8	14	15.2	16.5	17.7	18.9	20.1	21.3	22.5	23.7
60	2.3	3.7	5	6.4	7.8	9.1	10.5	11.9	13.3	14.6	16	17.4	18.7	20.1	21.5	22.8	24.2	25.6	27.0
66	2.6	4.1	5.6	7.2	8.7	10.2	11.8	13.3	14.9										
72	2.8	4.5	6.2	7.9	9.6	11.3	13.1	14.8	16.5										
78	3.1	4.9	6.8	8.6	10.5	12.3	14.2	16	17.8										
84	3.3	5.3	7.2	9.2	11.2	13.2	15.1	17.1	19.1										
90	3.5	5.6	7.7	9.8	11.9	14	16.1	18.2	20.3										
96	3.8	6.1	8.4	10.6	12.9	15.2	17.5	19.8	22										
102	4.1	6.5	9	11.4	13.9	16.3	18.8	21.2	23.6										
108	4.4	7	9.6	12.2	14.8	17.4	20	22.6	25.2										
114	4.6	7.3	10.1	12.8	15.6	18.3	21.1	23.8	26.5										
120	4.8	7.7	10.5	13.4	16.3	19.2	22	24.9	27.8										

Ratings

- Free Area: 8.1 ft^2, 50.1% , at 48 in. × 48 in. tested model size.
- **Performance***
  - Free Area Velocity: 781 FPM
  - Air Volume: 6,317 CFM
  - Pressure Loss: 0.10 in w.g.
- Velocity @ 0.15 in w.g. Pressure Loss: 971 FPM
- Design Load: 30 PSF

*Performance Rated at Beginning Point of Water Penetration

Water Penetration



Water penetration is measured as the free area velocity at the intersection of a simple linear regression of test data and the line of 0.01 ounces of water per square foot of free area. It is measured through a 48 in. × 48 in. louver over 15-minutes.

Intake louvers should be selected with a reasonable margin of safety below the beginning point of water penetration to avoid unwanted entry during severe storm conditions.

Beginning Point of Water Penetration = 781 fpm

Pressure Loss



Pressure drop is the difference in total pressure between two points of a fluid carrying network.

(904) 241-9944 | MoffittCorp.com

Moffitt continuously improves our products. Specifications and dimensions are subject to change.
®The Moffitt logo is a registered trademark of Moffitt in the U.S., Mexico, and Canada. | ©2026 Moffitt. All rights reserved. Version 1 | October 2026

S445-JE Wall Louver
ATTRIBUTES

Moffitt Ventilation Solutions



Vertical Section
Screen adds approximately
0.1875 in. to louver depth.



Visible Vertical Mullion
(standard)



Horizontal Mullion
(standard)



Flange Frame
(optional)

Additional Options



Blank-Off Options
Non-Insulated and Gasketed
1 in. Insulated (4.25 R-value)
2 in. Insulated (8.75 R-value)



Burglar Bars Shipped
Loose or Mounted



Filter Rack



Glazing Frame



Flashing Options
Head and Sill Available



Hinge and Subframe
Right or Left Side Option Available



Stucco Flange 0.75 in.
Standard Stucco Depth

(904) 241-9944 | MoffittCorp.com

Moffitt continuously improves our products. Specifications and dimensions are subject to change.
®The Moffitt logo is a registered trademark of Moffitt in the U.S., Mexico, and Canada. | ©2026 Moffitt. All rights reserved. Version 1 | October 2026